



Audio Speaker Cable



Description :

Description	Auto Speaker Cable
Conductor:	Stranded Copper Conductor of Class 5/6 (Flexible)
Insulation:	PVC Compound
Conductor Color	Red/Black, Transparent
Temperature Range:	-30 - 70°C
Nominal Voltage:	300/500V, 450/750V
Test Voltage:	2500 V
Standard	IEC 60552

Application :

1. All the cables are used for speaker ranges, home theater or audio system.
2. Used for connecting power amplifier and broadcasting systems.
3. Used for transmitting the audio signals amplified by the amplifier.



CABLE MANUFACTURER
HENAN SANHENG INDUSTRIAL CO., LTD.

Office Tel: +86-0371-53395807
Whatsapp/Wechat: +86-18135696936
Email: sanheng@sanheng.cc
www.electrical-cable.com

Technical Data :

Coresx nominal cross-section	Insulation colour	Conductor structure	External diameter	Conductor resistance at 20°C	Inductance	Cu weight	Cable weight
		nominal	approx.	max.	approx.		approx.
N x mm ²		n x mm	mm	Ω/km	[μH/m]	kg/km	kg/km
2 x 0,5	Red/black	16 x 0,20	2,4 x 4,8	390	0,58	9,6	21
2 x 0,75	Red/black	24 x 0,20	2,5 x 5	260	0,57	14,4	29
2 x 1	Red/black	32 x 0,20	2,6 x 5,2	19,50	0,56	19,2	32
2 x 1,5	Red/black	30 x 0,25	2,7 x 5,6	13,30	0,55	28,8	42
2 x 1,5	transp	84 x 0,15	2,7 x 5,6	13,30	0,55	28,8	42
2 x 1,5	transp	192 x 0,10	2,7 x 5,6	13,30	0,55	28,8	42
2 x 2,5	Red/black	50 x 0,25	3,6 x 7,4	7,98	0,53	48	61
2 x 2,5	transp	140 x 0,15	3,6 x 7,4	7,98	0,53	48	61
2 x 2,5	transp	320 x 0,10	3,6 x 7,4	7,98	0,53	48	61
2 x 4	Red/black	56 x 0,30	4,5 x 9,7	4,95	0,51	76,8	110
2 x 4	transp	224 x 0,15	4,5 x 9,7	4,95	0,51	76,8	110
2 x 4	transp	512 x 0,10	4,5 x 9,7	4,95	0,51	76,8	110
2 x 6	transp	192 x 0,20	6,1 x 12,5	3,30	0,50	115,2	141
2 x 6	transp	336 x 0,15	6,1 x 12,5	3,30	0,50	115,2	141
2 x 6	transp	768 x 0,10	6,1 x 12,5	3,30	0,50	115,2	141
2 x 10	transp	560 x 0,15	7 x 15	1,95	0,49	192	250
2 x 10	transp	1.280 x 0,10	7 x 15	1,95	0,49	192	250